



SEBINO NATURALE / POLISHED

FEATURES

ORIGIN Europe

STONE Sedimentary Limestone

CHARACTERISTICS A very faint and understated natural toned limestone with several small, minute granules ranging from light and medium browns and rusty-amber, to subtle cream and nude tones.

SIZE 3/8" (1cm), 1/2" (1.2cm), 3/4" (2cm), 1 1/4" (3cm)

RECOMMENDED USES Interior/exterior walls, interior/exterior floors, heavy traffic areas, fireplaces, columns, mouldings, etc.

POSSIBLE FINISHES Honed, Polished, Brushed, Sandblasted, Sandblasted+Brushed, Flamed, Flamed+Brushed, Bush Hammered.

Finishes are specific to each marble/stone type. Please inquire for finishes available.

CUSTOM SIZES MADE TO ORDER

TECHNICAL INFORMATION

Uniaxial Compressive Strength	67 MPa
Compression Resistance After Freeze Test	57 MPa
Flexural Strength	13.1 MPa
Volumetric Weight	2263 kg/cm ³
Water Absorption at Atmospheric Pressure	3.42 %
Open Porosity	7.70 %
Abrasion Resistance	21 mm
Slip Resistance - Dry	85 SRV
Slip Resistance - Wet	51 SRV
Reaction to Fire	A1 Class



315 Place d' Youville #268 Montreal, QC H2Y 2B5 514-613-0383 311 North Robertson Blvd. #920 Los Angeles, CA 90211 323-275-1007