

CITAL



SEBINO VERDE / POLISHED

FEATURES

ORIGIN Europe

STONE Sedimentary Limestone

CHARACTERISTICS A very faint and understated, gray-green limestone with several small, minute granules ranging in color from light and medium gray to subtle minty-greens with hints of rust and amber.

SIZE 3/8" (1cm), 1/2" (1.2cm), 3/4" (2cm), 1 1/4" (3cm)

RECOMMENDED USES Interior/exterior walls, interior/exterior floors, heavy traffic areas, fireplaces, columns, mouldings, etc.

POSSIBLE FINISHES Honed, Polished, Brushed, Sandblasted, Sandblasted+Brushed, Flamed+Brushed, Bush Hammered.

Finishes are specific to each marble/stone type. Please inquire for finishes available.

CUSTOM SIZES MADE TO ORDER

TECHNICAL INFORMATION

Uniaxial Compressive Strength	67 MPa
Compression Resistance After Freeze Test	57 MPa
Flexural Strength	13.1 MPa
Volumetric Weight	2263 kg/cm ³
Water Absorption at Atmospheric Pressure	3.42 %
Open Porosity	7.70 %
Abrasion Resistance	21 mm
Slip Resistance - Dry	85 SRV
Slip Resistance - Wet	51 SRV
Reaction to Fire	A1 Class

